

CUSTOM SERVICE & DESIGN, INC.

AUBURN HILLS, MI

Phone: 248.340.9005 Fax: 248.340.9002

www.customserviceanddesign.com


MULTI BAG VESSEL SPECIFICATION

BULLETIN: 3612-14

TWELVE BAG VESSEL DESIGN

CSD OFFERS A COMPLETE LINE OF FILTRATION VESSEL DESIGNS SETTING NEW STANDARDS IN THE INDUSTRY. THE TWELVE BAG VESSEL DESIGN UTILIZES 12 STANDARD #2 SIZE BAG FILTERS WITH FLOW RATES UP TO 2640 GPM.

CSD'S STATE-OF-THE-ART VESSELS
OFFER FILTRATION SOLUTIONS TO A VARIETY
OF INDUSTRIES AND APPLICATIONS. BAG
HOUSING DESIGNS EFFECTIVELY REMOVE
DIRT AND OTHER CONTAMINENTS FROM
PROCESS LIQUIDS OFFERING PARTICULATE
REMOVAL FROM 1 THRU 800 MICRON, LOW
DIFFERENTIAL PRESSURE DROPS AND COST
FEFECTIVE CLEAN FLUIDS.



APPLICATIONS:

CHEMICAL PROCESS
COATINGS & PAINT

COOLING TOWER

DI / RO WATER

ENVIRONMENTAL / GROUND REMEDIATION

FOOD & BEVERAGE

Manufacturing / Industrial

PHARMACEUTICAL POWER GENERATION


STANDARD FEATURES:

- ⇒ CARBON STEEL, 304L & 316L STAINLESS STEEL
- ⇒ PERMANENTLY PIPED VESSELS
- ⇒ STAINLESS STEEL RESTRAINER BASKETS
- ⇒ BAG HOLD DOWN BUILT INTO LID
- ⇒ 150 P.S.I.
- ⇒ MANUAL HYDRAULIC JACK LID LIFT
- ⇒ Outlets Available: Inline
- ⇒ FLANGED CONNECTIONS
- ⇒ VENT, GAUGE, DRAIN PORTS
- ⇒ Buna Seals
- ⇒ PERMANENT WELDED LEGS

OPTIONS:

- \Rightarrow Several Vessel Styles Available
- ⇒ Manual / Automatic Duplexing
- ⇒ SEAL MATERIAL: EPDM, VITON, TEFLON ENCAPSULATED VITON
- ⇒ Mesh Lined Restrainer Baskets
- \Rightarrow Higher Pressure Rating
- ⇒ DAVIT ARM LID LIFT
- ⇒ Low Profile
- ⇒ Specialty Designed Vessels





BAG SIZES	INDUSTRY STANDARD #2 BAGS; 12 BAGS PER UNIT						
BASKET LENGTH	30"						
BASKET MATERIAL	STAINLESS STEEL WITH 9/64" PERFORATION						
HOUSING LID	MANUAL HYDRAULIC JACK LID LIFT WITH 0.5" (F) NPT VENT PORT AND BUILT-IN BAG HOLD DOWN						
CONNECTION SIZE	6", 8", 10"						
CONNECTION STYLE	FLANGED						
INLET / OUTLET LOCATIONS	OUTLETS AVAILABLE: INLINE, OPPOSITE SIDE, SAME SIDE, LOW PROFILE						
SEALS	BUNA, EPDM, VITON, TEFLON ENCAPSULATED VITON						
CONSTRUCTION / FINISH	CARBON STEEL W/ STANDARD EXTERIOR FINISH; STAINLESS STEEL W/ BEAD BLAST SATIN FINISH						
PRESSURE RATING	150 PSI @ 250° F						
ADDITIONAL PORTS	FOUR 0.5" (F) NPT GAUGE PORTS; ONE 1.5" (F) NPT DRAIN PORT						
BASE	PERMANENT WELDED LEGS						

^{*} Based on vessel only. Please consider filter media, expected contaminant loading and fluid viscosity when sizing a filter vessel.

BUILD A CSD PART NUMBER

0	36	12	30	16L	100	F	4	В	С
TYPE	VESSEL SIZE	# OF BASKETS /	ELEMENT	# OF LUGS	CONNECTION	CONNECTION	OUTLET	SEALS	MATERIAL OF
		ELEMENTS	LENGTH		Size	STYLE	LOCATION		Construction

^{***} For specific vessel dimensional cut sheets, call factory or consult website***



CUSTOM SERVICE & DESIGN, INC.

AUBURN HILLS, MI

PHONE: 248.340.9005 FAX: 248.340.9002

